
CHEMICAL PROCESSING INDUSTRY

PRODUCT RECOMMENDATION GUIDE




Chemical Processing Product Recommendation Guide



Compressed Gasketing

- 3500 GYLON® 3500 PTFE gasketing for strong acids
- 3504 GYLON® 3504 PTFE gasketing for stainless steel flanges, heat exchangers, towers/reactors and centrifuges
- 3510 GYLON® 3510 PTFE gasketing for strong alkalies and acids; listed on Chlorine Institute Pamphlet 95
- 3535 Style 3535 PTFE joint sealant for plate exchangers and tower trays
- 3545 GYLON® 3545 100% pure, compressible PTFE gasketing for all types of flanges, especially glass-lined equipment and rail cars
- 15500 IFG® 5500 gaskets for saturated steam, oils, refrigerants, mild chemicals, aliphatic hydrocarbons, gasoline, inert gases and water
- 9064 Style 9064 white neoprene gasketing, 60 durometer, conforms to FDA 21CFR177.2600
- SS STRESS SAVER® gaskets for FRP, PVC, CPVC, and other types of nonmetallic flanges




and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury.

Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

Performance data published in this brochure has been developed fror field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

Metallic Gaskets



GRAPHONIC®, Kammprofile, and double-jacketed gaskets for shell and tube heat exchangers

TANDEM SEAL™ fire-safe, chemically inert, spiral wound gaskets

FLEXSEAL, GRAPHONIC, GUARDIAN, GYLON, IFG, ISO-GARD, KLOZURE, MILL-RIGHT, MODEL 64, P/S and STRESS SAVER are registered trademarks of Garlock Inc.

EQUALIZER, GUARDIAN, and TANDEM SEAL are trademarks of Garlock Inc.

Compression Packing

- 1303 Style 1303-FEP* braided graphite spool packing for all types of valves
- Style 1304 or 1333-G braided graphite spool packing for rotating equipment, tower trays and centrifuges
- 5888 Style 5888 for acid and chlorine valves on rail cars
- 5906 Style 5906 braided PTFE packing for food and pharmaceutical applications
- 9000 9000-S EVSP* cup-and-cone packing for all emission control valves subject to EPA regulations, especially high-pressure ethylene crackers

Expansion Joints

- 200 GUARDIAN® 200/200HP FEP-lined joints with abrupt arch configuration
- 214 Style 214/215 flexible PTFE pipe couplings, available in 1" to 8" sizes
- 306 GUARDIAN® 306 FEP-lined joints with wide flowing arch configuration

KLOZURE® Mechanical Seals

- 3D 3-D mixer/agitator seals compensate for extreme shaft movement. Up to 1" total indicated runout (TIR)
- Type 19 mixer seal designed for vertical mixers, and other equipment with excessive radial shaft movement
- 80 Type 80 balanced rotary seal for ANSI chemical pumps
- GMP GMP-I and GMP-II single or double cartridge seals for positive displacement and ANSI chemical pumps
- PSII P/S®-II multi-lip cartridge seals for positive displacement and progressive cavity pumps, ANSI chemical pumps, and mixers/reactors

KLOZURE® Oil Seals & Bearing Isolators

- Model 26 lip seals for centrifuges, positive displacement and ANSI chemical pumps
- 64 MODEL 64® and Model 87 severe service lip seals
- for centrifuges; available in fluoroelastomer, nitrile and MILL-RIGHT®
- EQUALIZER™ bearing isolators for high-speed centrifuge applications, ANSI pumps, and rotating equipment
- GDN GUARDIAN™ metallic bearing isolators for positive displacement and ANSI chemical pumps; available in bronze and stainless steel
- ISO-GARD® bearing isolators for positive displacement and ANSI pumps
- PSI P/S®-I lip seals for positive displacement and ANSI chemical pumps

^{*} Patent #4,328,974

Food and Pharmaceutical Applications - Typical Equipment

- Agitators
- Conveyors
- Dryers
- Mixers
- Pumps/motors

- Autoclaves
- Cookers
- Filter systems (screens)
- · Non-metallic piping
- Storage tanks

- Blenders
- Cooling vessels
- Homogenizers
- · Packaging/bottling

Sealing Components for FDA Compatibility (Examples only, not a complete list)

Gasketing

- Style 8316 EPDM gasketing
- Style 9064 neoprene gasketing
- STRESS SAVER® PTFE/EPDM gasketing
- GYLON® restructured PTFE gasketing, in various styles and fillers
- FLEXSEAL® spiral wound gaskets with 304 SS and PTFE filler

Stuffing Box Sealing

- PTFE compression packing Styles 5904 and 5906
- GMP-I and II cartridge mechanical seals
- P/S®-II cartridge mechanical seals with white GYLON® lips
- 3D mixer/agitator seals with white GYLON[®] lips

Radial Lip Sealing/Exclusion

- Model 23/53/63 lip seals with FDA-compliant silicone
- P/S®-I (Model 61) radial lip seals with FDA-compliant GYLON®
- ISO-GARD® bearing isolators with FDA-compliant filled PTFE

Expansion Joints

- GUARDIAN® 306 EZ-FLO™ expansion joints with FEP lining
- Style 206 EZ-FLO™ expansion joints with EPDM liner
- Styles 214/215 PTFE flexible couplings

Hydraulic Sealing

- Style 7500 CHEVRON® packing
- FDA urethane U-seals

Garlock offers the most complete line of FDA-compliant materials in the industry.

Please consult Garlock for details on FDA-compliant gasketing, packing, expansion joints, hydraulic components, etc., and KLOZURE® Dynamic Seals for oil seals, bearing isolators and mechanical seals.

AUTHORIZED REPRESENTATIVE

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

GARLOCK is a registered trademark for packings, seals, gaskets, and other products of Garlock.

© Garlock Inc 2007. All rights reserved worldwide.



an EnPro Industries company

Garlock Sealing Technologies 1666 Division Street Palmyra, New York 14522 USA 1-315-597-4811 1-800-448-6688 Fax: 1-800-543-0598 1-315-597-3039

www.garlock.com

Other Garlock facilities are located in:

Columbia, SC, USA Phone 1.803.783.1880 Fax 1.803.783.4279

São Paulo, Brazil Phone 55.11.4352.6161 Fax 55.11.4352.8181

Saint-Étienne, France Phone 33.4.7743.5100 Fax 33.4.7743.5151

SingaporePhone 65.6285.9322
Fax 65.6284.5843

Houston, TX, USA Phone 1.281.459.7200 Fax 1.281.458.0502

Sherbrooke, Canada Phone 1.819.563.8080 Fax 1.819-563.5620

Neuss, Germany Phone 49.2131.3490 Fax 49.2131.349.222

Shanghai, ChinaPhone 86.021.62789702
Fax 86.021.62787826

Sydney, Australia Phone 61.2.9793.2511 Fax 61.2.9793.2544

W. Yorkshire, England Phone 44.1422.313600 Fax 44.1422.313601

Mexico City, Mexico Phone 52.555.567.7011 Fax 52.555.368.0418

Dubai, UAEPhone 971.4.8833652
Fax 971.4.8833682